
P R O D U C T D A T A

02150
Metal Conditioner

DESCRIPTION:

02150 Metal Conditioner is a one-step cleaner, degreaser and phosphatizer for steel and aluminum substrates. Metal Conditioner will eliminate rust from steel substrates and is extremely effective in eliminating flash rusting on freshly blasted steel. Metal Conditioner eliminates oil, grease, and other low surface tension contamination and conditions the metal for exceptionally good adhesion of primer and paint.

TECHNICAL DATA:

PACKAGED VOC	132 g/l, 1.1 lbs/gal
VOC AS USED AS DIRECTED	12 g/l, 0.1 lb/gal
SHELF LIFE	one year (unopened)
FLASH POINT	150° F, 66° C
RECOMMENDED DILUTION FOR USE	1 part 02150 Metal Conditioner to 10 parts water

DIRECTIONS FOR USE: Mix 1 part 02150 Metal Conditioner with 10 parts water. Apply to metal substrate by wiping, mopping, pump sprayer, or pressure sprayer. Allow Metal Conditioner to condition metal for 5-10 minutes. Rinse with a 2% solution of Metal Conditioner in water (2 parts Metal Conditioner to 100 parts water). Allow substrate to completely dry before applying primer or paint.

DISCLAIMER: The technical information and suggestions for use have been compiled for your guidance and usage. Such information is based on Precision Coatings, Inc. experience and research and is believed to be reliable. As PCI has no control over conditions in which the product is used, stored, or otherwise handled, the above information does not constitute a warranty. Buyers must assume responsibility for the suitability of the product for their purposes.